

# SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/6

## ACTIVATOR CLP


Revision 0

Revision date 2015-05-22

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

<b>1.1. Product identifier</b>	
<b>Product name</b>	ACTIVATOR CLP
<b>1.3. Details of the supplier of the safety data sheet</b>	
<b>Company</b>	SEAL IT SERVICES LTD
<b>Address</b>	T/A BOND IT Unit G16 Riverbank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN
<b>Web</b>	www.bond-it.co.uk
<b>Telephone</b>	01422 315300
<b>Fax</b>	01422 315310
<b>Email</b>	sales@bond-it.co.uk
<b>1.4. Emergency telephone number</b>	
<b>Emergency telephone number</b>	01422 315300 8.30AM - 5.30PM Mon-Fri

### SECTION 2: Hazards identification

<b>2.1. Classification of the substance or mixture</b>	
<b>2.1.1. Classification - 67/548/EEC</b>	F+; R12 Xi; R38 N; R50/53 R67 Symbols: F+: Extremely flammable. Xi: Irritant. N: Dangerous for the environment.
<b>Main hazards</b>	Extremely flammable. Irritating to skin. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.
<b>2.1.2. Classification - EC 1272/2008</b>	Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 1: H410;
<b>2.2. Label elements</b>	
<b>Hazard pictograms</b>	
<b>Signal Word</b>	Danger
<b>Hazard Statement</b>	Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Skin Irrit. 2: H315 - Causes skin irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
<b>Precautionary Statement: Prevention</b>	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting// equipment.

## ACTIVATOR CLP

Revision 0

Revision date 2015-05-22

## 2.2. Label elements

<b>Precautionary Statement: Response</b>	P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P370+P378 - In case of fire: Use to extinguish. P391 - Collect spillage.
<b>Precautionary Statement: Storage</b>	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up.
<b>Precautionary Statement: Disposal</b>	P501 - Dispose of contents/container to meet National Legislation and Environmental Regulations

## SECTION 3: Composition/information on ingredients

## 3.1. Substances

## 67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Heptane {heptane} (n-Heptane)	601-008-00-2	142-82-5	205-563-8		20 - 30%	F; R11 Xn; R65 Xi; R38 R67 N; R50/53	

## EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Heptane {heptane} (n-Heptane)	601-008-00-2	142-82-5	205-563-8		20 - 30%	Flam. Liq. 2: H225; Asp. Tox. 1: H304; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Acute 1: H400; Aquatic Chronic 1: H410;	
Butane	601-004-00-0	106-97-8	203-448-7		1 - 10%	Flam. Gas 1: H220;	
Propane	601-003-00-5	74-98-6	200-827-9		1 - 10%	Flam. Gas 1: H220;	
N,N-Dimethyl-p-toluidine	612-056-00-9	99-97-8	202-805-4		0 - 0.5%	Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT RE 2: H373; Aquatic Chronic 3: H412;	

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

<b>Inhalation</b>	Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache. Move the exposed person to fresh air. Seek medical attention.
<b>Eye contact</b>	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
<b>Skin contact</b>	May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
<b>Ingestion</b>	Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

## 4.2. Most important symptoms and effects, both acute and delayed

## ACTIVATOR CLP

Revision 0

Revision date 2015-05-22

## 4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache.
Eye contact	May cause irritation to eyes.
Skin contact	May cause irritation to skin. May cause dermatitis.
Ingestion	Harmful if swallowed. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. Ingestion may cause nausea and vomiting.

## 4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	If swallowed, seek medical advice immediately and show this container or label.

## SECTION 5: Firefighting measures

## 5.1. Extinguishing media

	Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam.
--	---

## 5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.
--	---

## 5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

## SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Eliminate all sources of ignition. Wear suitable protective equipment.
--	---

## 6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

## 6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

## SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

## 7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.
--	--

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

## 8.1.1. Exposure Limit Values

Heptane (heptane) (n-Heptane)	WEL 8-hr limit ppm: 500	WEL 8-hr limit mg/m3: 2085
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

## ACTIVATOR CLP

Revision 0

Revision date 2015-05-22

## 8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Self-contained breathing apparatus. Wear protective clothing.

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Appearance	Aerosol
Colour	Colourless
Odour	Characteristic
pH	No data available
Melting point	No data available
Initial boiling point	No data available
Flash point	< -40 °C
Evaporation rate	No data available
Flammability (solid, gas)	Not relevant
Autoignition temperature	No data available
Explosive properties	No data available
Oxidising properties	No data available
Vapour pressure	No data available
Relative density	No data available
Partition coefficient	No data available
Viscosity	No data available
Vapour density	No data available
Fat Solubility	No data available
Solubility	Insoluble in water

## 9.2. Other information

Conductivity	No data available
Gas group	No data available
Surface tension	No data available

## SECTION 10: Stability and reactivity

## 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

## 10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

## 10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

## SECTION 11: Toxicological information

## 11.1.4. Toxicological Information

	No data available
--	-------------------

## SECTION 12: Ecological information

## 12.1. Toxicity

	No data available
--	-------------------

## ACTIVATOR CLP

Revision 0

Revision date 2015-05-22

## 12.3. Bioaccumulative potential

## Partition coefficient

ACTIVATOR CLP No data available

## SECTION 13: Disposal considerations

## General information

Dispose of in compliance with all local and national regulations.

## SECTION 14: Transport information

## Hazard pictograms



## 14.1. UN number

UN1950

## 14.2. UN proper shipping name

AEROSOLS

## 14.3. Transport hazard class(es)

ADR/RID	2
Subsidiary risk	see SP63
IMDG	2
Subsidiary risk	see SP63
IATA	2
Subsidiary risk	see SP63

## 14.4. Packing group

## Packing group

-

## 14.5. Environmental hazards

Environmental hazards	Yes
Marine pollutant	Yes

## ADR/RID

Hazard ID	-
Tunnel Category	(D)

## IMDG

EmS Code	F-D S-U
----------	---------

## IATA

Packing Instruction (Cargo)	203
Maximum quantity	150 kg
Packing Instruction (Passenger)	203
Maximum quantity	75 kg

## SECTION 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Authorisation and
-------------	--

## ACTIVATOR CLP

Revision 0

Revision date 2015-05-22

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

	Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EEC and 2000/21/EC.
--	--

**SECTION 16: Other information****Other information****Text of risk phrases in Section 3**

	R11 - Highly flammable. R38 - Irritating to skin. R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 - Harmful: may cause lung damage if swallowed. R67 - Vapours may cause drowsiness and dizziness.
--	--

**Text of Hazard Statements in Section 3**

	Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Skin Irrit. 2: H315 - Causes skin irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Flam. Gas 1: H220 - Extremely flammable gas. Acute Tox. 3: H301 - Toxic if swallowed. Acute Tox. 3: H311 - Toxic in contact with skin. Acute Tox. 3: H331 - Toxic if inhaled. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure . Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
--	--

**Further information**

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--