


Magic Gel



Product Range: Insulating and Sealing Gels

Application: Ideal for creating an IP68 protected connection when cast in suitable casings

Recommended For: Electrical Contractors, Lighting Installers, Maintenance Services, Security Services & Equipment



Quick cross linking in only 10 minutes



Suitable for any kind of installation, even underground or directly submerged

Scan to view
Product Video



Bi-component gel with very high dielectric and thermal characteristics, ideal for connection systems (joint shells or enclosures) for power cables

Quick cross linking, saving valuable time on-site

Non-toxic, safer for both the user and environment

No shelf life, does not expire over time

Working temperature -60 to 200°C, suitable for a wide range of environments



Re-enterable even after long working periods, allowing adjustments to be made easily

Low viscosity, surrounds and envelopes any type of material

IP68 Degree of protection when cast in suitable casings, able to replace all types of resin

Part Code	Stock Code	Description
MAGIC GEL 300	2020-1179	2 x 150ml Bottles
MAGIC GEL	0410-1847	2 x 500ml Bottles with Mixing Jug and Spatula
MAGIC GEL 10000	2020-1176	2 x 5L Tanks with Mixing Jug and Spatula

F4P®

Tel: **+44 (0)1302 765 570**
f4p-products.com @F4Pinfo