


Magic Power Gel

Product Range: Insulating and Sealing Gels

Application: Ideal for creating an IP68 protected connection when cast in suitable casings

Recommended For: Electrical Contractors, Lighting Installers, Maintenance Services, Security Services & Equipment



Quick cross linking in only 15 minutes



Effective in both vertical and ceiling applications

Quick cross linking,
saving valuable
time on-site

**Bi-component gel with
superior dielectric and
thermal characteristics,**
ideal for all types of
connections

Non-toxic,
safer for both
the user and
environment

Zero waste,
residual product can be
saved and used in
future applications

**Working temperature
-60 to 200°C,**
suitable for a wide
range of environments

**Strong self amalgamating
characteristics,**
provides exceptional sealing
properties in any condition

**Reusable as well as
re-enterable,**
allowing adjustments to
be made easily

**Single compact bottle
with convenient twin
compartment,**
takes up less space
in the toolbox

No shelf life,
does not expire over time



Part Code	Stock Code	Description
MAGIC POWER GEL 250	2020-1182	250ml Bi-Component Bottle
MAGIC POWER GEL 500	2020-1185	500ml Bi-Component Bottle with Mixing Jug and Spatula
MAGIC POWER GEL	1453-4977	1000ml Bi-Component Bottle with Mixing Jug and Spatula