

M18™ BRUSHLESS TWIN PACK



PERFORMANCE



82 Nm of torque and no load speed of 0 - 1.800 rpm

VERSATILITY



Impact range of 0 - 4,200 ipm with 180 Nm of torque



M18 REDLITHIUM™ More runtime, power and speed than standard lithium-ion batteries

ONLY

GREAT DEALS

SAVE £££'S

NEW PRODUCTS

FOR EVERY PRODUCT WITH AN MINEXT TO IT, WE* WILL DONATE THE AMOUNT STATED NEXT TO THE PRODUCT IN GREEN (PLUS VAT) TO MACMILLAN CANCER SUPPORT





390 STORES <u>NATION</u>WIDE



OVER 35,000 ITEMS IN STOCK ONLINE



OVER 300 BRANDS AVAILABLE









ELECTRICAL **EXPERTS**

IN-STORE | CEF.CO.UK | TRADE CATALOGUE | APP

M18™ BRUSHLESS TWIN PACK

[M18BLPD2] BRUSHLESS PERCUSSION DRILL

- Max. torque: 82 Nm
- No load speed: 0 550 / 0 1,800 rpm
- Impact rate: 0 28,800 bpm
- Max. drilling capacity: [Wood]: 76 mm [Metal]: 13 mm
 - [Masonry]: 16 mm
- Chuck capacity: Up to 13 mm

Weight with battery: 2.1 kg

- [M18BLID2] IMPACT DRIVER Max. torque: 180 Nm
- No load speed: 0 1,700 / 0 -2,600 / 0 3,400 rpm
- Impact rate: 0 1,500 / 0 3,400 / 0 4,200 ipm
- Drive size: 1/4" Hex
- Weight with battery: 1.7 kg

INCLUDES:

2 x Batteries: Li-lon 5 Ah
 Multi-volt fast charger
 Dynacase



MIZELEL



M12 FUEL™ INSTALLATION TOO

[FDDXKIT] 2612-0182

- Max. torque: 34 Nm
- No load speed: 0 1,600 rpm
- Variable speed settings: 2
- Max. drilling capacity: [Wood]: 28 mm [Metal]: 10 mm
- · Chuck capacity: Up to 10 mm



INCLUDES:

- 10 mm Metal chuck
- Right angle attachment
- Offset attachment
- 6 mm Hex attachment
- M12 Charger
- Dynacase



Milwauke

M18 FUEL™ SDS+ HAMMER



[M18CHX] 2176-6918

- Fixtec[™] keyless chuck system
- No load speed: 0 - 1,400 rpm
- Impact energy: 2.5J
- Impact rate: 0 - 5,100 bpm
- Max. drilling capacity: [Wood]: 30 mm

[Metal]: 13 mm [Masonry]: 26 mm

Weight with battery: 3.5 kg

- 2 x Batteries: Li-lon 5Ah
- Multi-volt fast charger
- Dynacase













M12TLI-lon INCLUDED WITH THE BODY ONLY TOOLS ON THIS PAGE

M12™ SDS+ HAMMER DRILL

[M12 H-0] 1494-0691

- Impact energy: 0.9J
- Impact rate: 0 - 5,350 bpm





M12 FUEL™ CUT OFF TOOL

[M12 FCOT-0] 2430-2812

- Disc diameter: 76 mm
- Max. cutting depth: 16.3 mm





M12™ IMPACT DRIVER

[M12 BID-0] 1829-6362

- Max. torque: 112 Nm
- Impact rate: 0 - 3,300 ipm



M12 FUEL™ **DIE GRINDER**

[M12 FDGA-0] 2624-4280

- No load speed [4 modes]: 0 - 24,500 rpm
- Collet capacity: 6 / 8 mm
- Max. grinding diameter: 50 mm





M12™ SUB COMPACT HACKZALL

[C12 HZ-0] 1173-4210

- No load speed: 0 - 3,000 rpm
- Stroke length: 13 mm



M12™ STAND LIGHT

[M12 SAL-0] 2527-3930

- Settings: High, medium, low and strobe
- Max. lumen output: Up to 1,400 lm
- Up to 10 hrs







M12™ SUB **COMPACT RIVET** TOOL

[M12 BPRT-0] 2430-2851

- Max. pulling force: 9,000 N
- Rivet diameter range: 2.4 - 4.8 mm



M12™ SOLDERING **IRON**

[M12 SI-0] 2375-7808

- Heater power: 90W
- Operating temperature: 400°C



M12™ VACUUM [M12 HV-01 2042-2369

Max. air volume:

934 l/min Max. vacuum: 31.1 mbar













M18™ ANGLE GRINDER

[HD18 AG-115-0] 1173-4198

Disc diameter: 115 mm





£149.95

MOFUEL

IMPACT DRIVER 1/2" [M18 FQID-0] 2262-1234

- 4 Mode drive control
- Impact rate: 0 1,800 / 0 - 2,900 / 0 - 4,000 ipm

M18 FUEL™ SURGE™

Max. torque: 50 Nm





M18™ BRUSHED SDS HAMMER DRILL

[M18 BH-0] 1829-6425



No load speed: 0 - 1,300 rpm

Impact energy: 1.2J









M18™ HEATGUN

[M18 BHG-0] 2293-8694



temperature: -18°C to 52°C Temperature

range: Up to 470°C



M18™ SDS+HAMMER DRILL

[HD 18 HX-0] 1235-2567



- Impact energy: 2.4J
- Impact rate: 0 - 4,200 bpm





M18 FUEL™ HACKZALL™

[M18 FHZ-OX] 2375-7802

No load speed: 0 - 3,000 rpm

Stroke length: 22 mm





M18™ HEAVY-DUTY METAL **BANDSAW**

[M18 HD18 BS-01 1173-4336




- Max. cutting capacity: 85 x 85 mm
- Blade length: 898.5 mm

UNIVERSAL DYNACASE BOX

2262-1057

Dimensions: 475 mm[L] x 358 mm[W] x 135 mm[D]



ONLY



18V XR BRUSHLESS COMBI HAMMER DRILL DRIVER

[DCD996M1-GB] 2571-1213

- Max. torque: 95 Nm
- Power output: 820W
- No load speed: 0 450 / 0 1,300 / 0 2,000 rpm
- Impact rate: 0 8,600 / 0 25,500 / 0 38,250 bpm
- Max. drilling capacity: [Wood]: 55 mm

[Metal]: 15 mm [Masonry]: 16 mm

Chuck capacity: Up to 13 mm

Weight with battery: 2.1 kg

INCLUDES:

- Battery: 4Ah Li-lon
- Multi-volt charger
- TSTAK Case



DEWALT

WHILE STOCKS LAST

ONLY

18V BRUSHLESS COMBI DRILL & IMPACT DRIVER TWIN PACK

DEWALT

2631-9085

IDCD7961 COMBI DRILL

- Max. torque: 70 Nm
- Power output: 460W
- No load speed: 0 550 / 0 2,000 rpm
- Max. drilling capacity: [Wood]: 40 mm

[Masonry]: 13 mm

- Chuck capacity: Up to 13 mm
- Weight with battery: 1.8 kg

IDCF8871 IMPACT DRIVER

- Max. torque: 205 Nm
- Power output: 400W
- No load speed: 0 1,000 / 0 - 2,800 rpm / 0 - 3,250 rpm
- Weight with battery: 1.5 kg



- 2 x Batteries: XR Li-lon 2Ah
- Multi-volt XR charger
- TOUGHSYSTEM Kit Box

















18V BRUSHLESS COMBI DRILL & ANGLE GRINDER TWIN PACK

DEWALT.

PLUS

100 PCE WALLDOGS

60 MM BIT HOLDER

25 PCE PZ2 BITS DIAMOND BLADE

WORTH £20

DEWALT

2631-9088

[DCD796] COMBI DRILL

- Max. torque: 70 Nm
- Power output: 460W
- No load speed: 0 550 / 0 2,000 rpm
- Max. drilling capacity: [Wood]: 40 mm [Metal]: 13 mm [Masonry]: 13 mm
- Chuck capacity: Up to 13 mm
- Weight with battery: 1.8 kg

[DCG405P2] ANGLE GRINDER

- Power output: 800W
- No load speed: 0 9,000 rpm
- Max. disc: 125 mm[Ø]
- Weight with battery: 1.75 kg

INCLUDES: 2 x Batteries: XR

- Li-Ion 5Ah

 Multi-volt XR charger
- TSTAK Deep Box









ONLY £319.95

18V COMPACT TASK LIGHT

[DCL077] 2631-9079

- 3 Light settings to maximise runtime
- Lumen output: 500 2.000 lm
- Integral tripod mount
- Multi-position handle
- IP54





INCLUDES:

Battery: XR Li-lon 2Ah

18V COMPACT BLUETOOTH RADIO

[DCR029] 2631-9082

- Integrated handle and external roll cage
- USB Charging port allowing mobile phone charging
- Compatible with all XR batteries
- Mains power





INCLUDES:

Battery: XR Li-lon 2Ah



DONATION



DEWALT. NAKED POWER TOOLS - EXPAND YOUR TOOL KIT

COMBI DRIL

GRINDER

DEWALT **18V BRUSHLESS**

DEWALT

[DCD796N] 2631-9091

0 - 550 /

0 - 2,000 rpm



[DCG450N] 2631-9097

- Max. disc: 125 mm[Ø]
- No load speed: 0 9,000 rpm
- Weight: 1.75 kg



ONLY DIAMOND

[DCF887N] 2631-9100

- Max. torque: 205 Nm
- Power output: 400W
- No load speed:
- 0 1,000 /0 - 2,800 rpm / 0 - 3,250 rpm
- Weight: 1.34 kg





ONLY

DEWALT

PLUS MM BIT HOLDER 25 PCE PZ2 BITS

ONLY

18V ELECTRIC STAPLER

IDCN701NI 2631-9103

- Compact design Fast actuation speed
- Magazine capacity:
- 35 staples Weight with battery:

INCLUDES:

540 Pce staples

DEWALT

18V XR HANDHELD LED WORKLIGHT

[DCL050] 2631-9094



- 9 Position articulating lamp head
- Extendable hanging hook Lumen output: 250 - 500 lm
- Weight with battery: 1.1 kg

DEWALT



DEWALT

2.1 kg

DEWALT

18V 5AH LI-ION **BATTERY**

[DCB184] 2631-9106

- LED state of charge indicator helps manage park charging
- No memory effect and virtually no self-discharge for maximum productivity
- Compatible with all DEWALT XR Li-lon tools



18V MULTI-VOLT CHARGER

[DCB115] 2631-9109

- Charges DeWalt 10.8V. 12V. 14.4V. 18V XR Li-lon batteries
- Charges 2Ah battery in 30 mins and 4Ah battery in 60 mins
- LED indicator



DEEP TSTAK **CASE**

ITSTAKVII 2631-9112

- 1 x Large and 1 x small compartment
- Compatible with TSTAK
- Water resistant
- Max. capacity: 30 kg











MULTIFUNCTION TESTER – FLUKE 1662

2185-2499

• On / Off switchable auto-start for RCD and loop test

- Voltage and frequency
- Wiring polarity checker detects broken N wires
- Insulation resistance
- Continuity and resistance
- Measure motor windings with continuity test
- Loop and line resistance
- Automatic RCD test sequence
- Prospective earth fault current
- Prospective short circuit current
- RCD switching time
- RCD tripping level [ramp test]
- Measures trip time and current for RCD type A and AC in one test
- IP40

- Zero adaptor
- Mains plug test lead
- 3 Wire lead set with probes and croc clips
- Padded carrying and waist strap
- Switched probe
- 6 x Batteries: AA LR6
- Hard carry case

















MULTIFUNCTION TESTER - MFT 1741

2315-1076

- Enhanced non-trip loop impedance measurement technology
- Built-in confidence meter
- Variable testing of RCD types: AC, A, S, Type B [DC], plus programmable and 3 phase RCDs
- Ramp test and auto RCD test
- EN 61010 CAT IV safety rating
- 2 and 3 Pole earth spike testing
- Insulation testing at 100V, 250V, 500V and 1 kV
- Continuity and resistance: 15 mA or 200 mA tests
- Internal memory and Bluetooth® communications
- Simple colour-coded test selection
- Adjustable buzzer threshold
- True RMS system voltage and frequency measurement
- IP54

INCLUDES:

- 3 Wire lead set with probes and croc clips
- Switched probe
- Mains plug test lead
- Neck strap
- Calibration certificate
- AC Battery charger
- 6 x NiMH Rechargeable batteries
- Soft pouch

















()T.I.S.

MULTIFUNCTION TESTER - TIS MFTECO

2612-5537

- Large LCD display [128 x 128 pixels]
- Auto start mode for easy testing
- Dual test buttons for left or right handed use
- TRMS for accurate measurements on noisy and distorted circuits
- Automatic RCD testing, from 6 mA to 1A
- Insulation, resistance, continuity, loop and line resistance
- Insulation testing at 50, 100, 250, 500 and 1,000V

Phase to phase loop testing

Phase sequence measurement

Earth resistance







- 3 Wire lead set with probes and croc clips
- Switched probe
- Mains plug test lead
- Neck strap
- Harness
- Batteries
- Carry case













MANUAL RANGING DIGITAL MULTIMETER

2264-5096

- Continuity test
- Diode test
- Data hold function

USB-C Charge cable

- Voltage range: 0 - 600V AC / DC
- Current range: 0 10A
- Resistance: 0 2 MΩ
- CAT III 600V

INCLUDES:

Test leads
 Batteries



Flexible gooseneck
 Hook

CIRCUIT BREAKER FINDER AND SOCKET TESTER

1735-9297

Padded EVA case

 Advanced micro processor locates the fuse / breakers accurately using the latest 2nd pass technology

 Transmitter also acts as a socket tester with buzzer

Non-contact voltage detection

 Two part kit: Transmitter and receiver

Buzzer and LED indication

CAT II 600V

AUTO-RANGING DIGITAL MULTIMETER 2148-9301

- True RMS
- Diode test
- Audible continuity test
- Data hold function
- Battery and resistance test
- Voltage range: 0 - 600V AC / DC
- Current range: 0 - 15A AC / DC
- CAT II 1,000V and CAT III 600V

INCLUDES:

Red / black test leads
 Battery: 9V





ΕΤΗΩ

INCLUDES:

Battery: 9V PP3



⊕T.I.5.



LIFETIME

FOR EVERY PRODUCT WITH AN MINEXT TO IT, WE* WILL DONATE THE AMOUNT STATED NEXT TO THE PRODUCT IN GREEN (PLUS VAT) TO MACMILLAN CANCER SUPPORT ** SEE BACK













2304-0319

- Current: 100A AC
- Compare feature
- Low pass filter
- Backlit display with digital bar graph
- Auto, data and peak hold
- Jaw opening: 40 mm[Ø]
- CAT III 300V
- EN 61010-1

INCLUDES:

- Carry case
- 2 x Batteries:1.5V Alkaline AAA / LR03







2 x Batteries: AAA







PROVING UNIT

ΕΤΗΩS Test Instruments

2148-9277

- Intelligent voltage ramp testing for voltage indicators and multimeters
- 5 Step nominal output voltages: 50 690V
- Non-contact voltage detector proving function
- Auto power On / Off
- Rugged heavy-duty protective surround





ONLY

ΕΤΗΩS

Test Instruments

INCLUDES:

6 x Batteries: AA

GREEN CROSS LASER LEVEL IP54

2369-4034

- Green beams are 4 times more visible than red beams of the same power output
- Projected lines: Cross
- Laser Class 2
- Accuracy: ± 0.3 mm / 1 m
- Self-levelling: Horizontal and vertical
- Visibility range: 30 m
- Operating time: 4 hrs
- EN 60825



INCLUDES:

- Magnetic tripod base
- 2 x Batteries: AA
- Carry case



AUDIBLE SOCKET TESTER

(1) T. I. S.

0453-1399

- Tests 13A sockets
- Simply plug in for visual and audible indication
- CAT II 600V
- EN 61010-1



NON-CONTACT VOLTAGE DETECTOR

1906-0420

- 50 1,000V AC Detection
- Green LED shows power is ON
- Red LED and audible tone when voltage is detected
- Auto power Off
- Cat IV 1,000V

INCLUDES:

2 x Batteries: AAA 1.5V



DUAL RANGE NON-CONTACT VOLTAGE DETECTOR

1906-0423

- 12 48V AC and 48 1.000V AC Detection
- 5 x LEDs: Higher voltage or proximity cause more to illuminate with audible indication
- Built-in torch
- Auto power Off
- Cat IV 1,000V

INCLUDES:

2 x Batteries: AAA 1.5V



NON-CONTACT VOLTAGE DETECTOR

2071-0129

- 12 1,000V AC Detection
- 5 x LEDs: Higher voltage or proximity cause more to illuminate with audible indication
- Built-in torch
- Auto power Off Cat IV 1.000V
- 2 x Batteries: AAA 1.5V









THERMAL IMAGING CAMERA

2606-4961

- Easy to use single button capture
- Colour palettes and blended image for analysis
- Colour screen: 56 mm TFT
- Spotmeter: Centrespot, auto hot or cold markers
- Integral memory: Store up to 6,000 images
- Temperature range: -20 to 300°C





INCLUDES:

- Charger adaptor
- USB Lead
- USB Mains charger
- 4GB Micro SD card
- SD Card adaptor
- Rechargeable battery: Li-Ion





Megger.

ONLY

()T.1.5.

2 YEAR

PAT TESTER

2465-1571

- Stores up to 3,000 test results
- Full QWERTY keyboard for fast data entry
- Automatically creates test result certificates
- Tests 110V, 230V and 415V appliances and equipment
- Battery and mains operation
- Class I, Class II, leads, polarity, 230V and 110V sub-leakage tests functionality
- Auto power Off





- Earth bond test lead
- IEC Test lead
- Plug lead probe and croc clips
- 110V 2P+E Socket to 13A plug adaptor
 Pass labels
- 110V 2P+E Plug to IEC socket adaptor
- Mains adaptor

- 8GB SD Card
- 8 x Batteries: AA
- Carry case













(erao)

SLIM

5 PCE VDE ERGO™ SLIM BLADE SCREWDRIVER SE

2292-6385

- Slim style with reduced blade diameter
- Three component handle for maximum user comfort
- Colour-coded handle for ease of selection
- 1.000V Rated
- VDE certified
- IEC 60900



- Pozi: PZ1 and PZ2
- Slotted: SL3, SL4 and SL5.5 mm





BAHCO

PCE VDE TRITON XLS ISULATED SCREWDRIVER SET

1035-8038

- Anti-roll design prevents tool loss
- Toughened alloy steel blade for excellent durability
- 1,000V Rated



SET CONTENTS:

- Pozi: PZ1 and PZ2
- Slotted: SI 2.5, SI 4 and SL5.5 mm





PCE VDE ERGO™

0103-1074

- Three component handle for maximum user comfort
- Colour-coded handle for ease of selection



SET CONTENTS:

- Pozi: PZO, PZ2 and PZ3
- Slotted: SL2.5, SL3, SL4 and SL5.5 mm



VDE INSULATED SLOTTED



1,000V Rated

IEC 60900 and



CODE	DESCRIPTION	PRICE
2173-2262	SL2.5 mm	£6.50
2173-2265	SL3 mm	£7.50
2173-2268	SL3.5 mm	£7.95
2173-2271	SL4 mm	£7.95
2173-2274	SL5.5 mm	£9.50





180 MM VDE COMBICUTTER 3MAX™

0620-9518

Wire stripping notches for damage free stripping of 1.5 and 2.5 mm² wire

- Wire bending anvil
- Pattress screw shear for damage free cutting of 3.5 mm pattress screws and 4 mm conduit cover screws
- Drop dorged chrome vanadium steel for strength and durability
- Integral thumb guard
- 1.000V Rated
- VDE certified



BAHCO

VDE ELECTRICIAN'S INSULATED COMBINATION

1906-0273

- Unique three part insulation
- · Crimping die behind hinge for superior leverage when crimping non-insulated connectors, lugs and terminals
- Toothed pipe grip for greater power
- Overall length: 225 mm
- Integral thumb guard
- 1.000V rated
- VDE certified



CABLE CUTTERS

- · Cuts and strips copper and aluminium wire
- Drop-forged carbon steel with mirror polished head



CODE SIZE PRICE 2152-2040 160 mm £12 50 2152-2043 200 mm £16.50

VDE HIGH-LEVERAGE



- Optimised cutting jaw geometry for increased cutting performance
- 33% Slimmer than previous model for greater accessibility in tight areas
- Integral thumb guard
- 1.000V Rated
- VDE certified



CODE	SIZE	PRICE
2177-9575	180 mm	£32.50
2177-9578	200 mm	£36.95



VDE COMPACT AGONAL CUTTERS

1711-8190

- Cuts finest strands as well as multicore cables and piano wires
- Large jaw opening width for thicker cables
- Chrome vanadium heavy-duty steel forged and oil hardened
- Integral thumb guard
- 1,000V Rated
- VDE certified











AUTOMATIC WIRE



0043-5718

- Heavy-duty construction with hardened steel blades
- For stripping flat and round cable and wire: 0.2 - 6.0 mm²
- Automatic wire size adjustment and stripping length stop for consistent results



2194-4785

- Cutting jaws, forged and hardened for an extended working life
- Rounded blade design minimises cable distortion
- · Cutting capacity: Copper and aluminium - up to 52 mm[Ø]



CRIMPING PLIERS

0043-6846

- For boot lace ferrules
- Safe and secure crimping
- Auto-stop ratchet releases when correct pressure is applied
- Terminal size: 0.14 2.5 mm²



PVC PIPE AND CONDUIT CUTTER

0018-6619

- Suitable for efficient cutting of PVC conduits, blue water mains, rubber hose and pneumatic pipe
- Strong, lightweight, fibre glass-reinforced polycarbonate body



ARMOURSLICE SWA

- · Robust metal alloy body for exceptional strength and durability For stripping cable 12 - 36 mm[Ø]
- Fast, clean, safe stripping of SWA cables - up to 50% quicker than conventional stripping methods
- Integrated spare blade holder for quick blade changes





SPARE BLADES AVAILABLE **IPACK OF 51**







MINIBOX LEVEL



2221-8460

- Lightweight aluminium frame with reinforced vial. retention
- Accuracy: ± 0.5 mm
- Shock absorbing end caps protect the frame
- Length: 100 mm





REDSTICK™ DIGITAL LEVELS

- PINPOINT™ measurement technology for advanced readability
- Accuracy: ± 0.03° to 0.10°
- REDLITHIUM™ rechargeable USB battery
- Adjustable tolerance for precision, standard or rough work
- PIN mode allows target lock-in for replicating measurements All metal hang hole









FOR EVERY PRODUCT WITH AN MINEXT TO IT, WE* WILL DONATE THE AMOUNT STATED NEXT TO THE PRODUCT IN GREEN (PLUS VAT) TO MACMILLAN CANCER SUPPORT ** SEE BACK



UNIVERSAL STRIPPING TOOL



2163-1927

- For the fast and precise dismantling and stripping of all common and damp-proof cables
- Stripping device for cross-sections 0.2, 0.3, 0.8, 1.5, 2.5 and 4 mm²
- Simplified insertion of single wires for stripping using location ridges



WATERPUMP PLIERS

KNIPEX

2393-3563

 Chrome vandadium heavy-duty steel forged and oil hardened

- Pushbutton and quick ratchet feature for fast and easy adjustment to any position
- Jaw capacity: 52 mm
- Length: 250 mm



ERGO™ THIN JAW ADJUSTABLE WRENCHES

- 40% Wider jaw opening than standard adjustable wrenches
- 45% Thinner jaws [4.5 mm] than standard for access to tight spaces
- Metric scale for accurate pre-adjusting
- Comfortable thermoplastic handle

CODE	LENGTH	JAW CAPACITY	PRICE
1382-8747	170 mm	32 mm	£18.95
1035-9274	218 mm	38 mm	£21.50







ENGEX

STAINLESS STEEL CABLE TIE GUN

2044-1578

- Automatic cable tie tensioner and cutter for stainless steel cable ties
- The tool will correctly tension the ties and automatically cut off the tail when this is achieved
- High-quality construction for a long service life
- Supplied with 200 mm x 4.6 mm stainless steel cable ties - Pack of 100



ENGEX







14 PCE VDE TORQUE SCREWDRIVER SET I





- Torque highly accurate to EN ISO 6789:3003 ± 6%
- Clear audio signal when the required torque is achieved
- Factory calibration certificate included
- 1.000V Rated

1831-1404

- VDE certified
- IEC 60900



SET CONTENTS:

- Plus / minus: PZ / SL1 and PZ / SL2
- Pozi: PZ0, PZ1 and PZ2
- Slotted: SL2.5, SL3.5, SL4, SL5.5 and SL6.5 mm
- Adjustable handle
- Adjustament key
- Storage pouch











103 PCE ½" AND ¼" SOCKET SET

2152-3273

• High performance alloy steel

SET CONTENTS:

- Hex bits: H3, H4, H5, H6, H7 and H8
- Phillips bits: PH1. PH2 and PH3
- Pozi bits: PZ1, PZ2 and PZ3
- Torx bits: T6, T8, T9, T10, T15, T20, T25, T30 and T40
- Ball point hex keys: 1.5, 2, 2.5, 3, 4, 5, 6, 8 and 10 mm
- Combination spanners: 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18 and 19 mm
- 5/16" Torx bits: T45, T50 and T55
- ½" Hex sockets: 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12 and 13 mm
- ½" Hex deep sockets: 7, 8, 9, 10, 11 and 13 mm
- ½" Locking extension bar: 100 mm
- ½" Universal joint
- ½" Spinner handle
- ½" Ratchet handle
- ½" Ratchet spanner
- 1/4" Bit holder: 1/4"
- ½" Hex x ½" square adaptor
- Locking bit adaptor: Hex ½" to hex ½"
- ½" Hex sockets: 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 24, 27, 30, 32 and 34 mm
- ½" Hex deep sockets: 10, 13, 16, 17, 18 and 19 mm
- ½" Extension bars: 125 and 250 mm
- ½" Breaker bar: 250 mm
- ½" Universal joint
- ½" Spark plug sockets: 16 and 21 mm
- ½" Ratchet handle
- ½" Bit holder: ½"
- Storage case



41 PCE ½" AND ¼" SOCKET SET

2152-3237

SET CONTENTS:

- Combination spanners: 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18 and 19 mm
- ¼" Hex sockets: 5, 5.5, 6, 7, 8, 9, 10, 11, 12 and 13 mm
- ½" Hex sockets: 10, 12, 13, 14, 15, 16, 17, 19, 21 and 24 mm
- ¼" Extension bar: 50 mm and 150 mm
- ½" Extension bar: 125 mm and 250 mm
- ¼" Sliding T-Bar
- ¼" Universal joint
- ½" Universal joint
- ¼" Ratchet handle
- 1/2" Ratchet handle
- Storage case









54 PCE SCREWDRIVER BIT SET WITH COLOUR-CODED



2292-6391

allov steel



- Hex bits: H3, H4, H5, H6 and H8
- Phillips bits [25 mm]: 1 x PH1. 4 x PH2. 1 x PH3 and 2 x PH2G
- Phillips bits [125 mm]: PH1 and PH2
- Pozi bits [25 mm]: 1 x PZ1. 4 x PZ2 and 1 x PZ3
- Pozi bits [125 mm]: PZ1 and PZ2
- Robertson bits: R1 and R2
- Slotted bits [25 mm]: SL4.5 and SL5.5 mm
- Tamper torx bits [25 mm]: TX10, TX15, TX20, TX25 and TX30
- Torx bits [25 mm]: 2 x T10, 2 x T15, 4 x T20, 2 x T25, 1 x T27, 4 x T30 and 1 x T40
- Torx bits [150 mm]: T20, T25 and T30
- Magnetic bit holder
- Ouick-release bit holder
- ¼" Hex to ¼" square socket adaptor
- Storage case





armed

TIC-TAC MAGNETIC SCREWDRIVER BI

- Magnetic collar locks onto the fastener
- Bit holds the fastener firmly at any orientation

 Handy dispenser box can be stacked together for convenience



Size: PZ2

Length: 50 mm







49 PCE SHOCKWAVE™ **DRILL SCREWDRIVER**

2610-6022

- Designed for use with impact drivers
- Reduces stress at the tip resulting in less tip breakages providing up to 30 x longer life



SET CONTENTS:

- Hex: 1 x H4 and 1 x H5
- Phillips: 3 x PH1, 3 x PH2 and 1 x PH3
- Pozi: 2 x PZ1. 6 x PZ2 and 1 x PZ3
- Slotted: SL4.5, SL5.5 and SL6.5 mm
- Torx: 4 x T10, T15, 5 x T20, T25, 4 x T30 and 1 x T40
- Drill bits: 3, 4, 5 and 6 mm [Hex base]
- Magnetic bit holder
- Storage case



32 PCE SHOCKWAVE™ **IMPACT DUTY BIT SET**



2407-9942

- Designed for use with impact drivers
- SHOCKZONE™ reduces stress at the tip resulting in less tip breakages

 Precision milled tip provides the best fit with screw head reducing cam out and stripping



SET CONTENTS:

- Hex bits: H3, H4, H5, and H6
- Pozi bits: 1 x PZ1. 2 x PZ2 and 1 x PZ3
- Phillips bits: 1 x PH1, 2 x PH2 and 1 x PH3
- Tamper torx bits: TX07, TX08, TX09. TX10. TX15. TX20 and TX25
- Torx hits: 2 x T10, 2 x T15, 3 x T20. 2 x T25, 2 x T30 and 1 x T40
- Locking bit holder
- Storage case











11 PCE DRY DIAMOND CORE DRILL SET

0278-8483

- For use on general concrete, soft bricks, lightweight blocks, natural stone and limestone
- For deep core drilling, with the ability to core through a standard brick in one action
- Ideal for drilling waste pipes, water feed pipes, cable entry / exit, flue passages, extractor fans, exhausts and dust extractor ducting
- Do not use with hammer action

SET CONTENTS:

- 5 x Dry diamond cores: 42, 52, 65, 117 and 127 mm[Ø]
- SDS+ and hexagon ½" BSP adaptor
- 200 mm ½" BSP Extension bar
- 400 mm Pilot drill
- 225 mm A-taper guide rod
- Draft pin
- Storage case



LDX METAL CUTTERS

armes

ACCELER8*MAX

- Ideal for steel plate, iron, aluminium, copper, cast iron, stainless steel, fibreglass and plastics
- Tungsten carbide teeth deliver excellent wear resistance
- Integral spring automatically ejects the slug for hasslefree drilling
- Use cutting oil to extend tooth life
- Use on rotation only: 300 - 1,000 rpm
- Max cutting depth: 5 mm

onoctoric modi
A STATE OF THE STA

PRICE

£24 95

£24.95

£31.50

FROM £**24.95** £**4.**95

MULTIPURPOSE WIPES

SIZE [MM]

20 mm

25 mm

32 mm

BIG WIPES

0165-6058

CODE

0278-9437

0278-9443

0278-9446

- Powerful cleaning with built-in skin care
- Dermatologically tested
- Anti-bacterial action
- Removes paint, adhesives, epoxy, PU foam, oil, grease and more from hands, tools and surfaces
- Pack of 80




ONLY £**8.25** £**V**AT

3 PCE SHEET STEEL HOLESAW KIT

2042-4118

 Suitable for use with impact drivers on mild / stainless steel and aluminium



 Internal spring automatically ejects the metal disc for hassle-free drilling

 Replacement springs and drive adaptor / pilot drill available – sold separately

- Constant pitch: 8 tpi
- Cutting depth: 38 mm

KIT CONTENTS:

- Holesaws: 20, 25 and 32 mm
- Drive pilotAllen key: 25 mm
- Spring
- Storage case

ONLY £41.50 +VAT

SUPER RE

armed

ACCELER H%

DUOXIM HOLE ENLARGING ARBOR

2265-0535

- Suitable for expanding existing holes by adding desired larger holesaw and then the original smaller holesaw for use as a guide
- Diameter: 40 mm
- Shank type: Hex

INCLUDES:

Pilot drill



FOR EVERY PRODUCT WITH AN MEXT TO IT, WE* WILL DONATE THE AMOUNT STATED NEXT TO THE PRODUCT IN GREEN (PLUS VAT) TO MACMILLAN CANCER SUPPORT** SEFERANCE OF THE PRODUCT OF THE PRODUCT OF THE PROPULATION OF THE PRODUCT OF THE PRODUCT



3 PCE PACKOUT™ STORAGE SET

2369-6758

PACKOUT™ ROLLING TROLLEY TOOLBOX

- Weight capacity: 113 kg [max]
- 228 mm[Ø] All-terrain wheels
- Industrial grade extension handle
- Metal reinforced locking point Interior organiser tray
- Dimensions: 560 mm[L] x 410 mm[W] x 480 mm[D]

PACKOUT™ LARGE TOOLBOX

- Metal reinforced top handle for easier carrying
- Metal reinforced locking point
- Impact resistant
- Interior organiser trays
- Dimensions: 560 mm[L] x 410 mm[W] x 290 mm[D]

PACKOUT™ TOOLBOX

- Metal reinforced locking point
- Impact resistant
- Interior organiser trays
- Dimensions: 560 mm[L] x 410 mm[W] x 170 mm[D]







PACKOUT™ CRATE

2621-5528

- Weight capacity: 22 kg
- Part of the PACKOUT™ modular storage system
- Large storage capacity for all kind of tools
- Dimensions: 450 mm[L] x 390 mm[W] x 250 mm[D]





PACKOUT™ DUFFEL BAG



2612-0545

- Part of the PACKOUT™ modular storage system
- Impact resistant base protects contents
- Dimensions: 380 mm[L] x 250 mm[W] x 340 mm[D]





CONTENTS NOT INCLUDED

PACKOUT™ COMPACT **TOOLBOX**

2624-4283

- Weight capacity: 34 kg [max.]
- Part of the PACKOUT™ modular storage system
- Quick adjust dividers to organise larger equipment and accessories
- Impact resistance
- IP65
- Dimensions: 441 mm[L] x 254 mm[W] x 330 mm[D]





Dimensions: 500 mm[L] x 120 mm[W] x 380 mm[D]

OVER 300 BRANDS

PACKOUT™ LARGE

ORGANISER







TECHNICIANS WHEELED

2425-3345

- Extra wide main compartment featuring a red lining for high tool visibility
- Zip down front panel featuring tool and A4 document storage
- Rugged and durable chassis, wheels and telescopic handle for all-terrain use
- No. of pockets: 30
- Dimensions: 500 mm[L] x 400 mm[H] x 300 mm[D]



DONATION

1906-0321

- Orange interior for easy tool visibility
- Large zip up pocket for securing small parts and tools
- 1680D Ballistic weave adds durability for making this great for use on-site
- Shoulder strap with extra padding
- Fully moulded bottom for stability and protection against the elements
- No. of pockets: 20
- Dimensions: 222 mm[L] x 222 mm[W] x 432 mm[H]



HEAVY-DUTY

2580-0331

- Wide opening for easy
- High visibility reflective strips
- Hard base for extra wear resistance
- No. of pockets: 20
- Dimensions: 440 mm[L] x 310 mm[H] x 250 mm[D]



ONLY

CABLE JACK PLUS

SUPER R

2560-9540



- Folds flat for convenient storage
- Multi-purpose work bench
- Max. carrying capacity: 70 kg



12 PCE TRADESMAN PRO™ TOOL KIT

- Extensive collection of the most commonly used tools
- 35 Pockets for maximum storage
- 1680D Ballistic weave adds durability making this great for use on-site
- Shoulder straps with extra padding for comfort

KIT CONTENTS:

- VDE Combination pliers 200 mm
- VDE Diagonal cutting pliers 200 mm
- VDE Slotted screwdrivers: SL2.5, SL4 and SL5.5 mm
- VDE Pozi screwdrivers: PZ1 and PZ2
- 7.5 m Double-hooked magnetic tape measure
- Aluminium torpedo spirit level
- Polymer cable rod set [1.32 m / 4.3 ft]
- Gekko gripper
- Tool bag





FIBREGLASS STEPLADDERS

- Suitable for professional trade use
- Independently tested to non-conductive 30,000V rating
- Integral tool rack
- Strengthened and deepened non-slip feet
- Static load rating: 150 kg [max]
- EN 131

	CODE	TREADS	CLOSED HEIGHT	OPEN HEIGHT	WEIGHT	PRICE
	0413-1247	4	1.17 m	1.1 m	6.25 kg	£59.95
	0413-1253	5	1.47 m	1.3 m	7.55 kg	£67.25
	0413-1259	6	1.77 m	1.6 m	8.50 kg	£73.95
_	0413-1262	8	2.37 m	2.2 m	11.5 kg	£97.50
M	0554-0167	10	2.87 m	2.7 m	15.05 kg	£127.95



FIBREGLASS HOP-UP

0697-5412

- Suitable for light trade use
- 600 x 600 mm Platform
- Easy set up, storage and transportation
- Double locking hinges for added safety
- Static load rating: 150 kg [max]
- Platform height: 480 mm
- No. of treads: 2



ENGEX

SCAFFOLD SAFETY TAG KIT

2150-1094

- Helps workers to identify if scaffold is safe
- Can be used as part of a daily inspection and monitoring procedure to record and manage scaffold inspections

KIT CONTENTS:

- Claw tag holder
- 2 x Inserts
- Permanent marker pen



0546-2692

Supplied with

individual padlocks

3 PART COMBINATION

0691-6276

- Extra wide stability bar
- Anti-slip feet
- · 'A' frame height: 1.59 - 2.39 m
- 'A' frame width: 1.06 m
- Static load rating: 150 kg [max]
- No. of treads: 18
- Open height: 3.37 m
- Closed height: 1.7 m
- EN 131





ENGEX

LADDER SAFETY TAG KIT

ENGEX

2150-1061

- Helps workers to identify if ladders are safe
- Can be used as part of a daily inspection and monitoring procedure to record and manage ladder inspections

KIT CONTENTS:

- Asset tag holder
- 2 x Inserts
- Permanent marker pen











VAN VAULT SLIDER

2567-8648

- Resistant top surface for stacking equipment and materials on top
- Heavy-duty roller bearings combined with full drawer runners
- Four reinforced fixing points with M10 bolts and shear nuts
- Floor mounts between wheel arches
- Fitted with a 70 mm anti-pick, anti-drill and anti-rust stainless steel disc lock
- Load capacity: 300 kg
- Fully phosphated and powder coated sheet steel
- Weight: 52.5 kg
- External dimensions: 500 mm[L] x 310 mm[H] x 1.200 mm[D]

INCLUDES:

70 mm Disc lock with 2 keys



16A FLOOR STANDING CABLE REEL 110V

0834-5095

- Trade and industrial power distribution for 110V appliances
- Impact resistant drum and toughened steel frame
- Recessed no shear sockets. neon power indicator and thermal cut out
- Cable length: 25 m
- IP44
- BS FN 61242:1998

INCLUDES:

- 110V 16A 2P+E Plug
- 2 x 110V 16A 2P+E Sockets



Defender



HEAVY-DUTY RUBBLE SACKS



2081-1088

- Double strength, heavy-duty rubble sacks
- Suitable for rubble, bricks, plaster, sand and gravel
- Size: 800 mm x 525 mm
- Pack of 6



VEHICLE FIRST AID KIT

1217-7277

- Suitable for vehicles with up to 3 passengers
- Supplied in a nylon, water-resistant pouch

KIT CONTENTS:

- 2 x Non-adherent dressing pads -5 cm x 5 cm
- Non-adherent pad 7.5 cm x 7.5 cm
- 20 x Assorted washproof plasters
- 2 x Triangular bandages
- Medium dressing Large dressing
- Resuscitation mouthshield with valve
- Gloves [pair]
- Finger bandage
- No. 16 eyepad
- 6 x Moist wipes
- Survival blanket



M firesafe

- Instant ice pack
- First aid scissors
- Conforming bandage - 7.5 cm x 4 m
- Microporous tape





DUST SHEE 2081-1067

 100% Absorbent cotton twill dust sheets

- Washable
- Size: 3.6 m x 2.7 m





COMPACT FOLDING LED WORKLIGHT

2576-1916

- Lumen output: 250 lm
- Additional 100 lumen top torch
- Beam range: 12 m
- 360° Rotating magnetic stand
- Run time: Up to 12 hrs
- IP20
- IK07 shock resistant

INCLUDES: • 3 x Batteries: AAA



4 FT LIGHT STICK & 110V **SPLITTER BOX**

1715-0281

- Wattage: 36W
- Lumens: 2.462 lm
- Anti-slip and weighted base
- Low-energy, high-output fluorescent task light
- Impact resistant polycarbonate lens
- 110V Four way splitter box for power distribution
- IP44



Defender

RECHARGEABLE LED

2429-7766

- Lumen output: 275 lm
- CREE LED
- 3 Light settings
- Beam range: 95 m
- Run time: 6.5 170 hrs
- Red LED's for night vision DONATION
- 45° Rotational head
- IPX5 Water resistant





TI UNILITE

AQUASAFE 16A IN-LINE CABLE CONNECTORS IP68

0134-2105

- Ouick connect and release with a snap lock collar
- Active latch mechanism for quicker wiring
- Operating temperature: -25 to 80°C
- IP68 to 2 Bar [equivalent to 20 m submerged]
- Cable range: 5 9 mm[Ø]
- IEC 61984



Defender

-40

22 M LED FESTOON GLS KIT 110V

- Suitable for indoor or outdoor use
- Polycarbonate LED lamps remove the risk of broken glass
- IP44

KIT CONTENTS:

- 10 x Lampholders
- 10 x Plastic guards
- 10 x 10W LED lamps [Daylight 6500K]
- 16A 110V 2P+E Plug





1.7 LTR JUG KETTLE

1689-3955

- Dual water gauge Safety locking lid
- Removable. washable filter
- Boil dry protection auto switch off
- Power rating: 2.2 kW



ONLY

igenix

700W MANUAL MICROWAV

igenix

2465-7907

- Capacity: 20 Ltr
- Power levels: 6 [including defrost]
- Timer: 30 mins
- Turntable: 245 mm[Ø]
- Dimensions: 386 mm[H] x 482 mm[W] x 294 mm[D]











TRADE HOODIE

- Adjustable hood with high neck for added warmth
- Abrasion resistant panels for long lasting durability
- Secure zipped pockets
- Ribbed hem and cuffs for a secure fit

SIZE
S
M
L
XL
XXL













TRADE BODY WARMER

- Lightweight and slim fitting
- Secure zipped pockets with internal pockets for added storage
- High collar and dipped back hem
- Material: 100% Nvlon

CODE	SIZE
2576-2810	S
2576-2813	M
2576-2816	L
2576-2819	XL
2576-2822	XXL







PRO BASE LAYER

- Skintight fit Moisture wicking
- Abrasion resistant
- Retains
- heat to help regulate body temperature
- Material: 92% Polyester, 8% elastane

CODE

1488-14 1488-14

1488-14

1488-14



	SIZE	
474	М	ONLY
477	L	10
480	XL	
483	XXL	± 1 4

PRO FLEX HOLSTER TROUSERS

- Flexible slim fit trousers for comfort and protection
- Abrasion resistant knee pockets with two pad position inserts
- Hanging and other multifunction pockets
- Triple stitched
- Material: 81% Polyester, 19% cotton

CODE	SIZE
2576-2747	W28", L30"
2576-2750	W30", L30"
2576-2753	W32", L30"
2576-2756	W34", L30"
2576-2759	W36", L30"
2576-2762	W38", L30"
2576-2765	W30", L32"
2576-2768	W32", L32"
2576-2771	W34", L32"
2576-2774	W36", L32"
2576-2777	W38", L32"
2576-2780	W40", L32"
2576-2783	W32", L34"
2576-2786	W34", L34"
2576-2789	W36", L34"
2576-2792	W38", L34"



PRO BASE LAYER **BOTTOMS**





- Abrasion resistant
- Elasticated waistband
- for comfort Retains
- heat to help regulate body temperature
- Material: 92% Polyester, 8% elastane

CODE	SIZE
1488-1462	М
1488-1465	L
1488-1468	XL
1488-1471	XXL





WORKER SOFTSHELL JACKET

scruifs

- Water resistant fabric with fleece lining to retain body heat for added comfort
- Secure zipped pockets

 Adjustable hood and high collar to protect against the elements

 Elasticated cuffs and hem for a secure and comfortable fit







CODE	SIZE	
2576-2795	S	
2576-2798	M	
2576-2801	L	
2576-2804	XL	
2576-2807	YYI	

olyester

ONLY 24.95 £24+VAT

CUT RESISTANT WORK



 13 Gauge grey HPPE and glass fibre liner

Cut resistance: Level 5

CODE	SIZE
2295-2170	L
2295-2173	XL





INKZALL™ MARKER

1917-9733

- Suitable for writing on dusty, wet or oily surfaces
- Clog resistant
- Ink colour: Black



WINTER ESSENTIALS PACK

scruifs

2576-2744

- Suitable for winter working conditions
- Soft breathable lightweight material
- One size fits all
- Machine washable
- Material: 100% Polyester





INCLUDES:

- Black fleece neck warmer
- Fleece work beanie
- Fleece gloves





ADJUSTABLE CLEAR

2295-2221

- Impact resistant polycarbonate lens
- Adjustable temple length
- UV Protection
- BS EN 166:2002



FFP2 DUST MASK



2628-2854

- Protection against toxic dusts, fumes and water based mists
- Adjustable nose piece and inner foam
- EN 149





X-MIST SANITISER SPRAY 250ML

2628-3703

- Eradicates stubborn odours
- Leaves a clean fresh smell
- Remains active for up to 7 days after use
- Kills 99.999% of bacteria





ONLY £13.29 +VAT













The easy way to shop for electrical products



390 STORES



OVER 35,000



TRADE CATALOGUE



TRADE APP
DOWNLOAD NOW



CLICK & COLLECT



PRE-ORDER & COLLECT

FOR EVERY PRODUCT WITH AN NEXT TO IT, WE* WILL DONATE THE AMOUNT STATED NEXT TO THE PRODUCT IN GREEN (PLUS VAT) TO MACMILLAN CANCER SUPPORT**



*CITY ELECTRICAL FACTORS ITD **A REGISTERED CHARITY IN ENGLAND AND WALES (261017) SCOTLAND (SC039907) & IN THE ISLE OF MAN (604), ADDRESS 89 ALBERT EMBANKMENT LONDON SE1 7UQ. PAID TO MACMILLAN CANCER SUPPORT TRADING LIMITED, A WHOLLY OWNED SUBSIDIARY OF MACMILLAN CANCER SUPPORT TO WHICH IT GIVES ALL OF ITS PROFITS.







YOUR ELECTRICAL EXPERTS IN-STORE | CEF.CO.UK | TRADE CATALOGUE | APP