

**GREAT DEALS** 

SAVE £££'S

**NEW PRODUCTS** 



OVER 390 STORES NATIONWIDE



OVER 35,000 ITEMS IN STOCK ONLINE



OVER 300 BRANDS AVAILABLE









YOUR ELECTRICAL EXPERTS 391 STORES | CEF.CO.UK | TRADE CATALOGUE



## FUEL™ WHEELED BAG 2262-1291

Dimensions: 540 mm [L] x 360 mm [W] x 290 mm [D]



ONLY £**45**:95

## UNIVERSAL DYNACASE BOX 2262-1057

Dimensions: 475 mm [L] x 358 mm [W] x 135 mm [D]



ONLY £**39**.95

## 18V FUEL™ 4 PCE SET



## M18FPD2 COMBI DRILL

- Max torque: 135 Nm
- No load speed: 0-550 / 0-2,000 rpm
- Impact rate: 0-32,000 ipm
- Max drilling capacity: [Wood]: 89 mm [Metal]: 16 mm [Masonry]: 16 mm
- Weight with battery: 2.2 kg

#### M18FID2 IMPACT DRIVER

- Max torque: 119 / 176 / 226 Nm
- No load speed: 0-1,900 / 0-2,800 / 0-3,600 rpm
- Impact rate: 0-1,200 / 0-3,400 / 0-4,300 ipm
- Drive size: 1/4" Hex
- Weight with battery: 1.7 kg

#### M18CHX SDS+ HAMMER DRILL

- No load speed: 0-1,400 rpm
- Impact energy: 2.5 J
- Impact rate: 0-4,900 ipm
- Max drilling capacity: [Wood]: 30 mm
  [Metal]: 13 mm
  [Masonry]: 26 mm
- Weight with battery: 3.5 kg

#### 4 M18CAG115XPDB ANGLE GRINDER

- Disc diameter: 115 mm
- No load speed: 0-8,500 rpm
- Spindle thread: M14
- Vibration: [Grinding]: 2.11 m/s²
  [Sanding]: 1.83 m/s²
- Weight with battery: 2.7 kg

#### **INCLUDES:**

- 2 x 18V 5.0Ah Li-lon Batteries
- Multi-Volt Charger
- Fuel™ Wheeled Bag



## 12V FUEL™ TWIN PACK

## 2580-8920

#### M12FPD SUB-COMPACT PERCUSSION DRILL

- Max torque: 44 Nm
- No load speed: 0-450 / 0-1,700 rpm
- Impact rate: 0-25,500 ipm
- Max drilling capacity: [Wood]: 35 mm [Metal]: 13 mm [Masonry]: 13 mm
- Weight with battery: 1.5 kg

#### M12FCOT CUT OFF SAW

- No load speed: 0-20,000 rpm
- Bore size: 10 mm
- Disc diameter: 76 mm
- Cutting depth: 16.3 mm
- Weight with battery: 1.1 kg

#### **INCLUDES:**

- 2 x 12V 2.0Ah Li-lon Batteries
- M12 Charger
- Dynacase























## **DCF887N 18V BRUSHLESS** IMPACT DRIVER

2327-5870

Max torque: 205 Nm

Impact rate: 0-3,800 ipm



## DCS331N 18V ORBITAL JIGSAW 1657-0717

Power output: 400W

No load speed: 0-3,300 spm



## DCS391N-XJ18V **CIRCULAR SAW**

2449-6564

 Power output: 760W Blade diameter: 165 mm

## DCD796N 18V BRUSHLESS **COMBI DRILL**

2269-6330

Max torque: 70 Nm

No load speed: 0-550 / 0-2,200 rpm



#### DCG412N 18V ANGLE GRINDER 1671-6853

Disc diameter: 125 mm

No load speed: 0-7,000 rpm



## Automatically adjusts based on cable thickness and staple

**ELECTRICIAN'S STAPLER** 

**DCN701N 18V** 

2574-7393

Bright LED for

enhanced visibility

## Working temperatures: 290 - 530°C Airflow: 109 - 190 l/min

DCE530N 18V HEAT GUN

2582-8822



## **AREA LIGHT** 2074-5235

**DCL050-XJ 18V LED** 

Lumen output: 250 - 500 lm

Runtime: Up to 10 hrs













DEWALT

# T-STAK CADDY WITH ANY 4 KITS PURCHASED FROM THIS PAGE

#### 25 PCE DRILL DRIVE SET 2571-1216

#### INCLUDES:

- Phillips [25 mm]: 2 x PH2
- Phillips [50 mm]: 1 x PH2
- Pozi [25 mm]: 5 x PZ2, 2 x PZ3
- Pozi [50 mm]: 1 x PZ2
- Torx [25 mm]: 1 x T10, T15, T20, 2xT25.1xT30
- Torx [50 mm]: 1 x T25 and T30
- HSS Drill Bits: 1 x 3, 4, 5 and 6 mm
- Magnetic Bit Holder
- Rapid Load Bit Holder



#### 31 PCE FLEXTORO SET 2582-8807

#### INCLUDES:

- Phillips [25 mm]: 2 x PH2, 1 x PH3
- Phillips [50 mm]: 1 x PH1, 3 x PH2
- Pozi [25 mm]: 1 x PZ1, 7 x PZ2, 1 x PZ3
- Pozi [50 mm]: 1 x PZ1, 7 x PZ2, 1 x PZ3
- Torx [25 mm]: T20 and T25
- Torx [50 mm]: T20, T25 and T30
- Magnetic Bit Holder



## 2582-8816

#### INCLUDES:

- Phillips [25 mm]: 1 x PH1, 3 x PH2 and 1xPH3
- Phillips [50 mm]: 2 x PH2
- Phillips [85 mm]: PH2
- Pozi [25 mm]: 2 x PZ1, 8 x PZ2 and 3 x PZ3
- Pozi [50 mm]: 1 x PZ1. 5 x PZ2 and 1 x PZ3
- Pozi [85 mm]: PZ2
- Slotted [25 mm]: SL4-6
- Torx [25 mm]: T20 and T25
- Torx [50 mm]: T20 and T25
- Torx Security [25 mm]: T25
- Magnetic Drive Guide





# 31 PCE FLEXTORO SET

## 2582-8810 **INCLUDES:**

- Phillips [25 mm]: PH2
- Phillips [57 mm]: PH2
- Pozi [25 mm]: PZ2
- Pozi [57 mm]: PZ2
- Torx [25 mm]: 1 x T10, 2 x T15, 4 x T20, 2 x T25 and 1 x T30
- Torx [57 mm]: 2 x T10, 3 x T15, 5 x T20 and 4 x T25
- Torx Security [25 mm]: T20 and T25

C E F ELECTRICAL

Magnetic Bit Holder

## 25 PCE DRILL DRIVE SET 2582-8804

## INCLUDES:

- Phillips [57 mm]: 2 x PH2
- Phillips [89 mm]: 1x PH2
- Pozi [25 mm]: 7 x PZ2, 1 x PZ3
- Pozi [57 mm]: 2 x PZ2, 1 x PZ3
- Pozi [89 mm]: 1 x PZ2
- Slotted [25 mm]: 1 x SL6
- Torx [25 mm]: 2 x T20, T25 and T30
- Torx [89 mm]: 1 x T20
- Socket Driver: 8 mm
- Magnetic Bit Holder

# 34 PCE FLEXTORO SET

## 2582-8813

## **INCLUDES:**

- Phillips [25 mm]: 1 x PH1, 2 x PH2 and 1 x PH3
- Phillips [57 mm]: 1x PH1 and 2x PH2
- Pozi [25 mm]: 1 x PZ1, 5 x PZ2 and 2 x PZ3
- Pozi [57 mm]: 1 x PZ1, 10 x PZ2 and 2 x PZ3
- Torx [25 mm]: T20 and T25
- Torx [57 mm]: 2 x T20 and 1 x T25
- Aluminium Magnetic Sleeve

## 18V FLEXVOLT SDS+ HAMMER DRILL

#### 2582-8825

#### DCH333-X254V FLEXVOLT SDS\* HAMMER DRILL

- No load speed: 0-1,000 rpm
- Impact energy: 3.5 J
- Impact rate: 0-4,480 ipm Max drilling capacity: [Wood]: 30 mm

[Metal]: 13 mm [Masonry]: 30 mm

- 3 modes: Rotary, rotary-hammer and chisel
- Weight with battery: 4.9 kg INCLUDES:
- 2 x 54V 9.0Ah XR FLEXVOLT<sup>TI</sup> Li-Ion Batteries
- Multi-Volt Charger
- T-Stack Carry Case


#### DCG412 18V ANGLE GRINDER Power output: 405W

- No load speed: 0-7,000 rpm Disc diameter: 125 mm
- Spindle thread: M14
- Vibration: 6.0 m/s<sup>2</sup>

3 Pce SDS+ Chisel Set.

250 Pce Mixed Hammer

Weight with battery: 2.2 kg









DEWALT

## 3 MODE SDS\* HAMMER DRILL

#### 3 MODE SDS+ HAMMER DRILL

- Power output: 710W
- No load speed: 0-1,550 rpm
- Impact energy: 2.0 J
- Impact rate: 0-5,680 ipm

2582-8831 / D25033K-LX 2582-8834 / D25033K-GB

- Max drilling capacity: [Wood]: 30 mm [Metal]: 13 mm [Concrete]: 22 mm [Core Bit]: 50 mm
- Weight: 2.5 kg

RIPTION	
110V	
24NV	2.40

OUGDS

Fixings Kit





QUADSAW

# **QUADSAW - SQUARE HOLE DRILL**

DESCRIPT

## 2565-0100

- Cuts holes to the standard size of single [75 x 75 mm] and double [75 x 135 mm] sockets
- Works with a drill driver [not impact driver] 2,000-2,500 rpm
- not hammer or percussion Cuts plasterboard, soundbloc, habito and fireboard
- [not fermacell or rigidur] Can cut into single or double skin plasterboard to maximum depth of 35 mm

#### **INCLUDES:**

- 6 x Blades Pilot Drill
- Spirit Level Carry Case



FREE DELIVERY

REPLACEMENT BLADE PACK

**INCLUDES:** 

Set of blades will cut hundreds of holes

Made from high grade German steel

2 x Long Blades 4 x Short Blades







**AMAZING DEALS & EXCLUSIVE SPECIAL OFFERS** 

## **MULTIFUNCTION TESTER**

## FLUKE 1662 / 2185-2499

- On / Off switchable auto-start for RCD and loop test
- Voltage and frequency
- Wiring polarity checker detects broken N wires
- Insulation resistance
- Continuity and resistance
- Measure motor windings with continuity test
- Loop and line resistance
- Automatic RCD test sequence
- Prospective earth fault current
- Prospective short circuit current
- RCD switching time
- RCD tripping level [ramp test]
- Measures trip time and current for RCD type A and AC in one test
- IP40

#### **INCLUDES:**

- Zero Adaptor
- Mains Plug Test Lead
- 3 Wire Lead Set with Probes and Croc Clips
- Padded Carrying and Waist Strap
- Switched Probe
- 6 x AA LR6 Batteries
- Hard Carry Case





# LEASING AVAILABLE **≡** 3 YEAR

FLUKE.

## **MULTIFUNCTION TESTER**

#### MFT1741 / 2315-1076

- Enhanced non-trip loop impedance measurement technology
- Built in confidence meter
- Variable testing of RCD types: AC, A, S, Type B [DC] plus programmable and 3 phase RCDs
- Ramp test and auto RCD test
- EN 61010 CAT IV safety rating
- 2 and 3 pole earth spike testing
- Insulation testing at 100V, 250V, 500V and 1 kV
- Continuity and resistance: 15 mA or 200 mA tests
- Internal memory and Bluetooth® communications
- Simple colour-coded test selection
- Adjustable buzzer threshold
- True RMS system voltage and frequency measurement
- IP54 **INCLUDES:**
- 3 Wire Lead Set with Probes and Croc Clips
- Switched Probe
- Mains Plug Test Lead
- Calibration Certificate
- Soft Pouch





**ONLY** 



EDITION COMPLIANT



Megger.

## **PROFESSIONAL THERMAL CAMERA**

## FLIR C2 / 2571-4210

- Pocket size, touch screen thermal camera
- Minimum focus distance: Thermal: 0.15 m

MSX [Multi-spectral dynamic lighting]: 1 m

- 4,800 pixels [80 x 60] infrared sensor
- Display size: 3"
- Display resolution: 320 x 240 pixels
- Object temperature range: -10 to 150°C
- Storage media: Internal memory stores at least 500 sets of images
- Supplied with FLIR tools reporting software for Mac or PC
- Dimensions: 125 mm [L] x 80 mm [W] x 24 mm [H]

















10





## **GREEN CROSS LASER LEVEL**

## 2369-4034

- Laser class: 2
- Accuracy: 0.3 mm per / m
- Number of beams: 2
- Direction of beams: Cross
- Visibility range: 30 m
- Weight with battery: 0.15 kg

## **INCLUDES:**

- Magnetic Tripod Base
- 2 x AA Batteries
- Carry Case









## LASER DISTANCE METER

## <del>⊕T.I.5.</del>

#### 2561-2171

- Measures up to: 40 m
- Measuring accuracy: ± 1.5 mm
- Measuring units: m / ft / in
- Area / Volume calculations
- Auto power off



## LINE SPLITTER **WITH LEAKAGE**

## 2576-2870

- Voltage: Up to 250V AC Current to 15A
- Separates the live conductor from the neutral and earth
- Enables safe measurement of current without the need to separate the conductors



## R1 / R2 SOCKET ADAPTOR

#### 0215-6422

- Plug-in adaptor for 4 mm standard test leads
- Safely and quickly obtain R1 and R2 measurements





ΕΤΗΩS

## **QUICK FIT LIGHTING ADAPTOR**

## 2389-6030

- A great edition to an electrician's toolbox which enables fast, easy safe connection of testing leads to light fittings
- Supplied with five adaptors suitable for BC, SBC, ES, SES and GU10

#### INCLUDES:

⊕T.I.5.

- 5 x Adaptors
- Red and Black Male to Male 4 mm Push Fit Leads



## <del>⊕7.1.5.</del> **DIGITAL SOUND LEVEL METER** 2037-5653 Decibel range: 30 - 130 dB Frequency: 30 Hz - 8 kHz Digital and bar graph display Auto range and auto power off Backlit display 2 YEAR

## 5 PCE VDE ERGO™ SLIM **BLADE SCREWDRIVER SET**

## 2292-6385

- Made from high performance alloy steel
- 30% Slimmer blades for greater accessibility
- ERGO™ 3 component handle for maximum user comfort with colour coded symbol on handle end
- 1,000V rated
- VDE certified

#### **INCLUDES:**

- Pozi: PZ1 and PZ2
- Slotted: SL3, SL4 and SL5.5 mm



## ВАНСО 5 PCE VDE TRITON XLS SCREWDRIVER SET

## 1035-8038

- Made from high performance alloy steel
- Large soft grip tri-lobe handle
- Precision machined tips to reduce the risk of tip breakage
- 1,000V rated
- Tip type marking for easy identification
- VDE Certified

#### INCLUDES:

- Pozi: PZ1 and PZ2
- Slotted: SL2.5, SL4 and SL5.5 mm



## 6 PCE VDE SCREWDRIVER SET

## 2191-0588

- Made from high performance alloy steel
- Dual component, soft grip handle for user comfort
- 1.000V rated
- VDE certified

#### **INCLUDES:**

- Pozi: PZ0. PZ1 and PZ2
- Slotted: SL3. SL4 and SL5.5 mm



## **VDE COMBI-TIP TWIN PACK**

#### 2152-3618

- Made from high performance alloy steel
- Colour coded handle
- 1,000V rated
- VDE certified

#### **INCLUDES:**

- Combi-tip PZ1 / SL5 mm
- Combi-tip PZ2 / SL6 mm








12









## **SOCKET BOX TEMPLATE**

## 2296-4056

- Quick and accurate positioning of single and double electric socket boxes
- Adjustable height guide up to 450 mm to comply with Building Regulations [Part M]
- Integrated level vial for accurate alignment

## 14" HARDPOINT SAW

#### 2152-3705

2152-3741

**INCLUDES:** 

ERGO™ handle

Length: 200 mm

Engineering Files:

and Round

Plastic Wallet

Hand, Half Round

- Cuts a variety of wood based materials, laminates, plastics and aluminium
- for 45° and 90° marking guide

- Compact design will fit into toolbox

Comfortable 2 component

handle for excellent grip



# 12" PROFESSIONAL HACKSAW FRAME



## 2227-5103

- Soft grip handle
- Alternative 55° blade mounting for flush cutting
- Steel tube core with plastic covering allows high blade tension for straight and accurate cuts
- Teeth per inch: 24









Rapid (

## **R28 TACKER**

## 2577-3211

(ergo

- Designed for low voltage cable up to 50V and 4.5 mm [Ø]
- Adjustable impact force INCLUDES:
- 2.000 x No.28 Staples and Case







# PVC PIPE AND CONDUIT CUTTER

## 0018-6619

- Glass fibre reinforced polycarbonate body
- Razor sharp stainless steel blade
- For efficient cutting of PVC conduit, blue water mains, plastic pipe, rubber hose and pneumatic pipe
- Max cutting capacity: 28 mm [Ø]



## **QUICK ADJUST SLIP JOINT PLIERS**

## 2152-2535

- High performance alloy steel
- Hardened teeth [60-62 HRC]
- Narrow head design
- Up to 35% bigger mouth opening
- Quick-adjust patented mechanism with auto tightening device on pipes and nuts
- Jaw capacity: 70 mm
- Length: 300 mm

## **ERGOSTRIP® UNIVERSAL DISMANTLING TOOL**

## 2163-1927

- Suitable for dismantling and stripping all common round and damp-proof installation cables, data and coax cables
- Conical, slimmed down tool ends perfect for use in confined areas
- Stripping device for cross-sections 0.2, 0.3, 0.8, 1.5, 2.5 and 4 mm<sup>2</sup>
- Location ridges simplify insertion of single wires



## **AUTOMATIC WIRE STRIPPER**

#### 0043-5718

- Integrated wire cutter and crimping jaws stripping wires: 0.2 - 6.0 mm
- Designed for fatigue free, repetitive stripping of flat and round cable and wire: 0.2 - 6.0 mm<sup>2</sup>
- Hardened steel blades



## STAINLESS STEEL **CABLE TIE GUN**



#### 2044-1578

- Automatic cable tie tensioner and cutter for stainless steel cable ties
- The tool will correctly tension the ties and automatically cut off the tail when this is achieved
- High quality construction for a long service life
- Supplied with 200 mm x 4.6 mm stainless steel cable ties - Pack of 100





PACK OF 100 CABLE TIES













## **5 PCE REVERSIBLE RATCHET COMBINATION SPANNER SET**

#### 2348-1637

- High performance alloy steel with chrome plated matt finish
- Open end angle 15° with slimmer head for accessibility
- Ratchet end with 12 points Dynamic Drive™ profile and 5° action angle

#### **NCLUDES:**

- Spanners: 8, 10, 13, 17 and 19 mm
- Plastic Case

## 160 mm VDE X-CUT® COMPACT **DIAGONAL CUTTERS**

## 1711-8190

- Cuts precisely even through fine copper wires
- Large opening width for thicker cables
- Great stability with 25% less weight Doubly supported joint axis
- 1.000V Rated
- VDE certified



## 180 mm VDE COMBICUTTER 3MAX™

## 0620-9518

- Wire stripping notches for effortless and damage free stripping of 1.5 and 2.5 mm<sup>2</sup> wire
- Wire bending anvil for quick and damage free doubling back of copper wire
- Pattress screw shear for damage free cutting of 3.5 mm pattress screws and 4 mm conduit cover screws

16



## **ERGO™ WIDE JAW ADJUSTABLE WRENCH**



 Black finish, precision hardened and anti-corrosion treated

Non-slip handle

 40% wider jaw opening than standard adjustables





## 140 mm SUPER KNIPS® XL

**BAHCO** 

#### 2299-8595

- For ultra fine cutting work
- Ground, very sharp cutting edges without bevel
- Opening spring and limiter
- Cutting edge hardness: Up to 64 HRC



## **TWINKEY®**

#### 1711-6066

- Multifunctional key for use in engineering, heating, gas and water supply shut-off systems
- Weight optimised zinc die-cast design
- Unique key suitable for use on lamp posts
- Reversible bit: SL7 mm and PH2
- 2 x 4-Way spider keys



**BAHCO** 

## 25 PCE ¼" METRIC **SOCKET SET 4-13 MM**

## 2152-3186

## **INCLUDES:**

- ½" Hex Sockets: 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12 and 13
- Phillips: 2 x PH2
- Torx: T10, T15, T20, T25, T30 and T40
- Hex: 5 and 6 mm
- ¼" Bit Holder with Locking Spring
- 100 mm Wobble Extension Bar
- Plastic Case















## **25 PCE RED-COBALT METAL DRILL BIT SET**

1120-7371



- Metal drill bits ground from solid extremely heat resistant cobalt-alloyed high speed steel produced according to DIN 338
- Polished finish

#### INCLUDES:

- Drill Bits: 1, 1.5, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5, 6, 6, 5, 7, 7, 5, 8, 8, 5, 9, 9, 5, 10, 10, 5, 11, 11, 5, 12.12.5 and 13 mm
- Storage Case

2190-4669





## 40 PCE SHOCKWAVE™ SET





#### 25 MM LENGTH

- Phillips: 1 X PH1 and 2 x PH2
- Pozi: 1 X PZ1 and 3 x PZ2
- Slotted: SL4, SL5.5 and SL6.5 mm
- Hex: H4 and H5 mm
- Torx: 2 x T10, 1 x T15, 3 x T20, 2 x T25, 1 x T30, 1 x T40 and 1 x T50 50 MM LENGTH
- Phillips: PH2
- Pozi: PZ1 and PZ2
- Torx: T10, T15, T20, T25 and T30

#### **INCLUDES:**

- Hex ¼": 3. 4 and 5 mm
- Bit Holders: 60 mm and 152 mm
- Magnetic Nut Drivers: 8 mm and 10 mm
- Storage Case



## 33 PCE SHOCKWAVE™ SET



2190-4573



#### 25 MM LENGTH

- Phillips: 1X PH1. 2x PH2 and 1x PH3
- Pozi: 2 x PZ1, 3 x PZ2 and 2 x PZ3
- Torx: 2 x TX10. 2 x TX15. 3 x TX20. 2 x TX25. 2 x TX30.1 x TX40 and 1 x TX50

#### 50 MM LENGTH

- Phillips: PH2
- Pozi: PZ2
- Torx: TX15, TX20 and TX25

SHOCKWAVE IMPACT DUTY MAGNETIC **NUT DRIVERS: 48 MM** 

- Hex: H7. H8 and H10 mm INCLUDES:
- Bit Holder: 60 mm
- Storage Case



# 32 PCE TWISTER™ SCREWDRIVER BIT SET

## 2042-4079

#### **INCLUDES:**

- Phillips: PH1, 2 x PH2 and PH3
- Pozi: PZ1, 2 x PZ2 and PZ3
- Slotted: SL3, SL4, SL5 and SL6
- Hex: H3. H4. H5 and H6
- Torx: T10, T15, T20, T25. T27, T30 and T40
- Tamper Torx: TX10, TX15, TX20, TX25, TX27, TX30 and TX40
- Click and Drive Adaptor
- Plastic Storage Case





## armed 27 PCE SOCKET & **SCREWDRIVER BIT SET**

## 2042-4016

## **INCLUDES:**

- Phillips: PH1, PH2 and PH3
- Pozi: PZ1, PZ2 and PZ3
- Slotted: SL4, SL5.5 and SL6.5 mm
- Hex: H3, H4, H5 and H6
- Tamper Torx: TX10, TX15, TX20, TX25 and TX30
- Sockets: 5, 6, 7, 8, 10 and 13 mm
- ¼ Hex x ¼ Square Adaptor
- Click and Drive Adaptor
- Access All Areas Ratchet



## **LOCKING BIT HOLDER**



- Optimised SHOCKZONE™ absorbs up to 3 x more torque
- Dual internal magnets ensure magnetism to fasteners
- Auto-locking one-handed bit release



CODE	DESCRIPTION	PRICE
2293-1143	73 mm	£5.95
2292-9568	152 mm	£6.95
2292-9571	305 mm	£7.95

# 11 PCE PZ2 SCREWDRIVER

#### 2042-4073

T W STER

- Click and drive adaptor for rapid bit changes
- Impact rated screwdriver bits for use with impact screwdrivers **INCLUDES:**
- Click and Drive Adaptor
- Pozi: 10 x 25 mm PZ2 Bits



armed

## 25 PCE SHOCKWAVE™ **PZ2 SCREWDRIVER BITS**

## 2190-4558

- Suitable for impact drivers
- Heat treated for increased durability INCLUDES:
- 25 x 25 mm PZ2 Bits



armed

## **6 PCE TIC-TAC MAG SCREWDRIVER BITS**

- 50 mm Bits feature a magnetic collar which locks onto the fastener
- Bit holds the fastener firmly at any orientation
- Handy dispenser box contains 6 Mag-Bits and can be stacked together for convenience















## CABLE DISPENSER

## 2560-9543

Easily load and draw cable from the reel

F4P

- Reel rotates on its own axis whilst stationary
- Designed to be used with most popular reels
- Lightweight, sturdy and compact
- Trouble free wiring



## **CABLE JACK PLUS**

## 2560-9540

- Dispense cable from various size spools
- 3 Poles provided
- Folds away flat for convenient storage
- Load capacity: 70 kg



# **METAL CAVITY FIXINGS & SCREWS**

## 2081-1169

#### **INCLUDES:**

- 200 x Metal Plasterboard Fixings
- 200 x Screws
- 2 x P72 Bits





## **REDSTICK BACKBONE MAGNETIC LEVEL**

- Durable frame with reinforced vial retention
- Accuracy: + / -0.5 mm
- Amplified rare earth magnets for maximum holding power
- Precision milled measuring surface
- Overmolded, non-slip grips stick to the wall and prevent sliding
- Shock absorbing end caps protect the frame
- All metal hang hole for storage



CODE	SIZE [MM]	PRICE
2262-1324	400	£39.95
2262-1327	600	£44.95
2262-1333	1,000	£54.95



## **ALUMINIUM MAGNET LEVEL**

#### 2152-3738

- Solid anodized aluminium level with 45° and 30° angles
- Accuracy: +/- 0.5 mm
- Rare earth magnetic base and machined surfaces
- Length: 250 mm





## 3 PCE PACKOUT™ STORAGE SET

#### 2369-6758

PACKOUT™ ROLLING TROLLEY TOOLBOX

- Weight capacity: 113 kg [max]
- 228 mm [Ø] All-terrain wheels
- Industrial grade extension handle
- Metal reinforced locking point
- Interior organiser tray
- IP65
- Dimensions: 560 mm [L] x 410 mm [W] x 480 mm [D] PACKOUT™ LARGE TOOLBOX
- Metal reinforced top handle for easier carrying
- Metal reinforced locking point
- Impact resistant
- Interior organiser trays
- IP65
- Dimensions: 560 mm [L] x 410 mm [W] x 290 mm [D] PACKOUT™ TOOLBOX
- Metal reinforced locking point
- Impact resistant
- Interior organiser trays
- IP65
- Dimensions: 560 mm [L] x 410 mm [W] x 170 mm [D]

## **PACKOUT™ TROLLEY**

## 2576-2864

- Weight capacity: 113 kg [max]
- Designed to easily roll with a heavy load on jobsite
- Metal reinforced locking points
- Dimensions: 480mm [L] x 620 mm [W] x 210 mm [D]



## 16" ZIP CASE

#### 2349-3580

- Multiple elastics in base and lid for tool retention
- Inside netting for holding documents and small tools Front and side card holder
- Rubberised handle
- Dimensions: 400 mm [L] x 90 mm [H] x 300 mm [D]





## **PACKOUT™ MOUNT**

#### 2576-2867

- Securely mount & stabalis Packout™ Organisers
- Weight Capacity: 45 kg
- Impact resistant
- Dimensions: 550 mm [L] x 390 mm [H] x 5 mm [D]




## PACKOUT™ SLIM ORGANISER



## 2528-2744

- 10 Removable storage bins
- Impact resistant IP65
- Dimensions: 500 mm [L]





## PACKOUT™ LARGE ORGANISER

#### 2363-2879

- 10 Removable storage bins
- Impact resistant
- IP65
- Dimensions: 500 mm [L]  $x 120 \, mm \, [H] \, x \, 380 \, mm \, [D]$















## 12 PCE TRADESMAN PRO™ TOOL KIT

## 2580-4114


## **INCLUDES:**

#### BACKPACK:

- 35 Pockets for maximum storage
- 1680D Ballistic weave for durability
- Shoulder straps with extra padding for comfort VDE SCREWDRIVERS:
- Slotted: SL2.5. SL4 and SL5.5 mm
- Pozi: PZ1 and PZ2

## **VDE PLIERS:**

- 1,000V 200 mm Insulated Diagonal Pliers
- 1,000V 200 mm Insulated Combination Pliers TOOLS:
- 7.5 m / 24.5 ft Double Hooked Magnetic Tape Measure
- Aluminium Torpedo Level Rare Earth Magnet
- Polymer Cable Rod Rod Set [1.32 m / 4.3 ft]
- Gekko Gripper



1ST OCT - 31ST DEC 2019

## TRADESMAN PRO™ WIDE OPEN TOOL BAG

#### 2467-3582

- Stav-open top for unobstructed tool access
- Orange interior and a wider opening to find tools easily
- Large interior zipper pocket
- Equipped with various sized pockets for tools and gear
- Multiple exterior front and back pockets for quick access
- Outside mesh pockets and metal tape measure holder
- 1680D Ballistic weave for durability
- Shoulder strap with extra padding and handles
- Fully moulded bottom protects from the elements
- Dimensions: 260 mm [L] x 413 mm [H] x 451 mm [D]

## 12" ELECTRICIAN'S HARD BOTTOM POUCH

#### 2152-3666

- Specifically designed for electricians
- Waterproof base
- Internal and external pockets
- Plastic box hidden in the bottom section
- Adjustable padded shoulder strap and soft grip handle
- Dimensions: 285 mm [L] x 285 mm [H] x 190 mm [D]



**BAHCO** 

## 18" OPEN TOTE BAG

## 2152-3672

- Waterproof base
- Adjustable padded shoulder strap
- Soft-grip handle
- 10 internal and 11 external pockets with tape measure clip and spirit level straps
- Dimensions: 410 mm [L] x 300 mm [W] x 240 mm [D]



## **FIBREGLASS** STEP LADDERS

- Suitable for professional trade use
- Independently tested to non-conductive 30,000V rating
- Integral tool rack
- Strengthened and deepened non-slip feet
- Static load rating: 150 kg [max]
- Complies to EN 131







CODE	TREADS	CLOSED HEIGHT [MM]	OPEN HEIGHT [MM]	WEIGHT [kg]	PRICE
0413-1247	4	1,174	1,050	6.25	£56.95
0413-1253	5	1,474	1,330	7.55	£62.95
0413-1259	6	1,773	1,610	8.50	£69.95
0413-1262	8	2,373	2,161	11.35	£91.95
0554-0167	10	2,870	2,700	15.05	£119.95

Prices are subject to VAT.

ENGEX

## 3 PART COMBINATION LADDER

#### 0691-6276

- 4 Adjustable positions
- Fully extended: 3.37 m
- Height in A frame: 1.59 2.39 m
- Width in A frame: 1.06 m
- Extra wide stability bar with non-slip feet

ENGEX

- Static load rating: 150 kg [max]
- Complies to EN 131



## LADDER SAFETY TAG KIT

#### 2150-1061

- Helps workers to identify if ladders are fit for purpose before use
- Can be used as part of a daily inspection and monitoring procedure to record and manage ladder inspections
- Size: 181 mm [L] x 50 mm [W]



## SCAFFOLD TAG KIT

#### 2150-1094

Helps to prevent accidents on site

 With current legislation requiring regular inspections, the tags enable scaffolders and construction site managers to easily document and monitor records in one place

Size: 180 mm [L] x 75 mm [W















## **VAN VAULT SLIDER**

#### 2567-8648

- Solid steel body with phosphated anti-corrosion protection
- Reinforced slip resistant top to take loads e.g pallets and materials
- Heavy-duty roller bearings combined with full drawer runners
- Weight capacity: 300 kg
- Floor mounts between wheel arches
- Fitted with a 70 mm anti-pick, anti-drill and anti-rust stainless steel disc lock
- Supplied with 3 keys and steel grip handle for easy opening
- The Slider is certified by Sold Secure and Secured by Design, the UK's Police approved standard
- Size external: 500 mm [L] x 312 mm [H] x 1205 mm [D]



## **VAN LOCK** & HASP

## 2057-1601

- Shrouded steel shackle padlock
- 6 Pin cylinder
- Heavy-duty steel construction with fixing bolts for security and convenience
- Integral storage bracket for secure storage of the lock when open



## **DE-ICER** SPRAY 500ML

#### 0284-1010

 Screen cleaning made easy on frosty mornings





# **SCREENWASH**

#### 1193-2192

- Ideal for removing traffic film and road dirt without smearing
- Protection to -3°C





## PORTABLE SITE LIGHT

## 2562-9964

- Lumen output: 2750 lm
- White COB LED
- Powerbank facility
- 180° adjustable handle
- Runtime: Up to 11 hrs
- 3.5 hours charge time
- Beam range: 88 m
- IP54 dust and

water resistant



## RECHAGEABLE LED HEADLIGHT

## 2429-7766

- Lumen output: 275 lm
- CREE LED
- 3 light settings
- Beam range: 95 m
- Red LED's for night
- vision on or flashing
- 45° rotational head
- IPX5 water resistant



## **FOLDING** SPEAKER LIGHT

## 2576-1928

- Lumen output: 750 lm White COB LED 300 lm Torch LED
- Beam range: 36 m
- Runtime: 4 154 hrs
- Charge time: 6.5 hrs
- 180° Adjustable handle / hook / stand
- Built-in wireless bluetooth speaker
- Strong magnets within base
- IPX4 water resistant

#### **INCLUDES:**

USB Type C Charging Cable



## COMPACT **WORK LIGHT**

## 2562-9955

- Lumen Output: 1.000 lm White COB LED 300 lm Torch LED
- Runtime: 4 84 hrs
- Charge Time: 6.5 hrs
- 180° Adjustable handle / hook / stand
- Strong magnets within base
- IPX5 water resistant

#### INCLUDES:

Micro USB Charging Cable



## 22W LED **UPLIGHT & 110V SPLITTER BOX**

## 2576-2825

- Lumen output: 2500 lm
- 180° light spread can be increased to 360° if reflector removed
- Base and uplight easily detach for ease of handling and storage
- 4 Way splitter base can be used independently
- Supplied with 3 m of rubber cable and 16A plug
- IP44
- Dimensions: 1,580 mm [H], Base 160 x 160 mm





- 2 x 20W twin heads
- Lumen output: 3.600 lm
- Colour temperature: 6500K
- Adjustable aluminium tripod: 910 - 1810 mm
- Site light can be detached from tripod

FAITHFULL



## 22 M GLS LED FESTOON KIT

#### 1279-5172

- A great solution for lighting site walkways
- Fully insulated
- Light spread: 240° INCLUDES:
- 22 m Hanging Light Chain
- 10 x Fittings and Guards
- 10 x 10W LED Lamps [800 lm each]















## PRO FLEX HOLSTER TROUSERS

- Flexible slim fit with comfort gusset
- Abrasion resistant top loading ballistic cordura knee pockets with two knee pad positions and knee ventilation
- Hammer loop, tool loops, velcro tool strap at waist and D-ring
- Cargo, rule, mobile phone and secure zipped pockets
- Triple stitched seams for long lasting durability
- 81% polyester, 19% cotton, 250 gsm

CODE	SIZE
2576-2747	W28", L30"
2576-2750	W30", L30"
2576-2753	W32", L30"
2576-2756	W34", L30"
2576-2759	W36", L30"
2576-2762	W38", L30"
2576-2765	W30", L32"
2576-2768	W32", L32"
2576-2771	W34", L32"
2576-2774	W36", L32"
2576-2777	W38", L32"
2576-2780	W40", L32"
2576-2783	W32", L34"
2576-2786	W34", L34"
2576-2789	W36", L34"
2576-2792	W38", L34"



# **COBRA SAFETY** GLASSES & I GOGGLE KIT

## 1598-5192

#### **INCLUDES:**

 3 x Cobra Lenses [Clear, Smoke and ESP] Pair of Arms

C E F YOUR ELECTRICAL EXPERTS

- Adjustable Strap
- Interchangeable Comfort Foam
- Case

26





## scruifs **LAYER TOP**

scruifs

1<sup>ST</sup> OCT - 31<sup>ST</sup> DEC 2019

- 4 Way stretch thermal engineered fabric
- Skin tight fit
- Moisture wicking
- Abrasion resistant
- Retains heat to help regulate
- body temperature
- 92% polyester, 8% elastane



CODE	SIZE
1488-1474	М
1488-1477	L
1488-1480	XL
1488-1483	XXL

## PRO BASE **LAYER BOTTOMS**

- 4 Way stretch thermal engineered fabric
- Skin tight fit
- Moisture wicking
- Abrasion resistant
- Elasticated waistband for comfort
- Retains heat to help regulate body
- temperature
- 92% polyester 8% elastane



	SIZE	
2	М	ONLY
5	L	
8	XL	
1	XXL	EIU+V

## **WORKER SOFTSHELL JACKET**

- Water resistant fabric with fleece lining to help retain body heat for added comfort
- Secure zipped pockets
- Adjustable hood and high collar to protect against the elements
- Elasticated cuffs and hem for a secure and comfortable fit
- Ideal for layering in cold conditions
- 100% polyester, 270 gsm

CODE	SIZE
2576-2795	S
2576-2798	М
2576-2801	L
2576-2804	XL
2576-2807	XXL



## TRADE HOODIE

- Adjustable hood with high neck for added warmth
- Abrasion resistant panels in key areas for long lasting durability - cut off and forearm

scruffs

- 2 x Secure zipped pockets
- Ribbed hem and cuffs for a secure fit
- Ideal for lavering
- 65% Polyester 35% cotton brushed back fleece, 320 gsm



CODE	SIZE
2393-0899	S
2393-0902	М
2393-0905	L
2393-0908	XL
2393-0911	XXI

## **TRADE BODYWARMER**

- Lightweight and slim fitting
- Hard wearing nylon fabric for long lasting durability
- Secure zipped pockets with 3 x internal pockets for added storage
- High collar and dipped back hem
- Ideal for layering
- 100% Nylon body, 96% polyester, 4% elastane softshell panels

CODE	SIZE
2576-2810	S
2576-2813	М
2576-2816	L
2576-2819	XL
2576-2822	XXL



## **VINTAGE BOBBLE HAT NAVY**

## 2078-6125

Lining with soft micro-fleece and padded with 3M thinsulate for maximum warmth

One size





CODE 1488-146 1488-146 1488-146 1488-147

















